

CERAMIC AUXILIARIES

DOLAPIX FF 44

Dispersant and deflocculant

Chemical basis: Phosphate preparation

Characteristics:

Appearance:	grey powder
Solubility:	partly water-soluble
Bulk density:	approx. 300 g/l
pH (10 %):	approx. 6.5
Na ₂ O:	approx. 7 %
Residue on ignition:	approx. 80 %

Shelf-life / Packaging:

6 months under proper and dry conditions bags of 20 kg

Application:

DOLAPIX FF 44 is a phosphate preparation, which is used for the deflocculation of refractory bodies.

DOLAPIX FF 44 shows a broad deflocculation interval and is also effective in cement-bonded bodies.

It is particularly suitable for dispersing microsilica containing, alumina bonded self-flowing castables.

The required addition quantity ranges between 0.1 and 1.0% of the whole mix.

The above results have been obtained from trials in our laboratory and plant. In the light of changing conditions they can serve only as a guide and are therefore offered without obligation. We ask you to observe the possible rights of third parties.

Version:04/05/2018

Zschimmer & Schwarz GmbH & Co KG Chemische Fabriken Page 1 / 1

Max-Schwarz-Straße 3–5 56112 Lahnstein | DE T +49 2621 12-485 F +49 2621 12-503 keramik@zschimmer-schwarz.com zschimmer-schwarz.com